



EPOXY PROJECT QUOTE REQUEST

GH Alaska, LLC has over 25 years' experience installing epoxy floors in Alaska.

(907) 414-4941 • techakrscllc@gmail.com

NAME: _____ DATE: _____

PHONE: _____ BEST TIMES TO CALL: _____ TEXTS OK

EMAIL: _____

MAILING ADDRESS: _____ CITY: _____ STATE: _____ ZIP: _____

PROJECT ADDRESS: _____ CITY: _____ STATE: _____ ZIP: _____

Commercial Residential (Please provide detailed directions if your Project Address doesn't show up accurately on Google Maps.)

PROJECT TYPE	<input type="checkbox"/> Hangar	<input type="checkbox"/> Kitchen	DIMENSIONS: Length x Width _____ x _____	COMPLETION DATE DESIRED: _____	
	<input type="checkbox"/> Garage	<input type="checkbox"/> Basement			TOTAL Square Feet (S/F): _____
	<input type="checkbox"/> Shop	<input type="checkbox"/> _____			TYPE OF HEAT: <input type="checkbox"/> In-Floor <input type="checkbox"/> Overhead <input type="checkbox"/> Baseboard

FLOORING OPTIONS DESIRED:

<input type="checkbox"/> Flake (Includes solid color base coat) Colors: 1. _____ 2. _____ 3. _____ <input type="checkbox"/> Special Order Flake Blend: _____	Flake Broadcast: <input type="checkbox"/> Full <input type="checkbox"/> Medium <input type="checkbox"/> Light Flake Size: <input type="checkbox"/> 1/4" <input type="checkbox"/> 1/8" <input type="checkbox"/> 1/16"	<input type="checkbox"/> Metallic (Includes solid color base coat) Colors: 1. _____ 2. _____ 3. _____
<input type="checkbox"/> Single Solid Tint Only (Does not include flake or metallic) Color: _____	<input type="checkbox"/> Quartz (Usually used on commercial floors) Color: _____ Granule Size: <input type="checkbox"/> 25A <input type="checkbox"/> 40S	
<input type="checkbox"/> Rubber/Vinyl Wall Base Height: <input type="checkbox"/> 4" <input type="checkbox"/> 6" Total Linear Feet (L/F): _____ Color: _____	<input type="checkbox"/> Embedded artwork, signage, or striping Description: (Please attach photo or graphic.) _____ _____	
<input type="checkbox"/> Polished & Sealed Concrete*	<input type="checkbox"/> Stained & Sealed Concrete*	

* NOTE: Sealing concrete does not prevent stains and must be re-sealed periodically, requiring greater maintenance than epoxy coatings. Epoxy floors provide more protection and durability.

Samples of flooring options may be seen at our affiliate: Alaska Resin Supply, 201 E. Swanson Ave., Suite 1, Wasilla, AK • M-F, 9-5

Interactive Tool: **VISUALIZE YOUR SEAMLESS FLOORING:** <https://www.torginol.com/design/>

SUBSTRATE: Concrete: Date/Year installed** _____ Gypcrete Wood Tile Other _____

** New concrete must cure 28 days before prepping with diamond grinders for epoxy.

Moisture or efflorescence issues with flooring or foundation—describe: _____

72-hour moisture testing is conducted prior to installation to determine if a moisture vapor transmission primer coat is required.

Efflorescence: If water is present in concrete, white or grayish crystalline salt deposits can form when water evaporates.

Grease or oil spots—describe: _____

PHOTOS: Please email pictures of the proposed installation space to our Estimator at techakrscllc@gmail.com.

How did you hear about GH Alaska? _____