



# EPOXY PROJECT QUOTE REQUEST

GH Alaska, LLC has over 25 years' experience installing epoxy floors in Alaska.

(907) 414-4941 • ghak.estimator@gmail.com

NAME: \_\_\_\_\_ DATE: \_\_\_\_\_

PHONE: \_\_\_\_\_ BEST TIMES TO CALL: \_\_\_\_\_  TEXTS OK

EMAIL: \_\_\_\_\_

MAILING ADDRESS: \_\_\_\_\_ CITY: \_\_\_\_\_ STATE: \_\_\_\_\_ ZIP: \_\_\_\_\_

**PROJECT ADDRESS:** \_\_\_\_\_ CITY: \_\_\_\_\_ STATE: \_\_\_\_\_ ZIP: \_\_\_\_\_

Commercial  Residential (Please provide detailed directions if your Project Address doesn't show up accurately on Google Maps.)

<b>PROJECT TYPE</b>	<input type="checkbox"/> Hangar	<input type="checkbox"/> Kitchen	<b>DIMENSIONS:</b> Length x Width _____ x _____	<b>COMPLETION DATE DESIRED:</b> _____	
	<input type="checkbox"/> Garage	<input type="checkbox"/> Basement			<b>TOTAL Square Feet (S/F):</b> _____
	<input type="checkbox"/> Shop	<input type="checkbox"/> _____			<b>TYPE OF HEAT:</b> <input type="checkbox"/> In-Floor <input type="checkbox"/> Overhead <input type="checkbox"/> Baseboard

## FLOORING OPTIONS DESIRED:

<input type="checkbox"/> <b>Flake</b> (Includes solid color base coat) Flake Colors: 1. _____ 2. _____ 3. _____ <input type="checkbox"/> Special Order Flake Blend: _____	Flake Broadcast: <input type="checkbox"/> Full <input type="checkbox"/> Medium <input type="checkbox"/> Light Flake Size: <input type="checkbox"/> 1/4" <input type="checkbox"/> 1/8" <input type="checkbox"/> 1/16"	<input type="checkbox"/> <b>Metallic</b> (Includes solid color base coat) Metallic Colors: 1. _____ 2. _____
<input type="checkbox"/> <b>Single Solid Tint Only</b> (Does not include flake or metallic) Color: _____	<input type="checkbox"/> <b>Quartz</b> (Usually used on commercial floors) Color: _____ Granule Size: <input type="checkbox"/> 25A <input type="checkbox"/> 40S	
<input type="checkbox"/> <b>Rubber/Vinyl Wall Base</b> Height: <input type="checkbox"/> 4" <input type="checkbox"/> 6" Total Linear Feet (L/F): _____ Color: _____	<input type="checkbox"/> <b>Embedded artwork, signage, or striping</b> Description: (Please attach photo or graphic.) _____ _____	
<input type="checkbox"/> <b>Polished &amp; Sealed Concrete*</b>	<input type="checkbox"/> <b>Stained &amp; Sealed Concrete*</b>	

\* NOTE: Sealing concrete does not prevent stains and must be re-sealed periodically, requiring greater maintenance than epoxy coatings. Seamless epoxy coatings won't collect dirt, moisture or germs and provide greater protection, sanitation and durability.

**SUBSTRATE:**  Concrete: Date/Year installed\*\* \_\_\_\_\_  Gypcrete  Wood  Tile  Other \_\_\_\_\_  
\*\* New concrete must cure 28 days before diamond grinder prepping.

Known moisture or efflorescence issues with flooring or foundation—describe: \_\_\_\_\_  
72-hour moisture testing is conducted prior to installation to determine if a moisture vapor transmission primer coat is required.

Sealer, coating or paint on floor:  Yes  No    If yes, describe: Manufacturer/Product: \_\_\_\_\_

Grease or oil spots—describe: \_\_\_\_\_

Samples of flooring options may be seen at our affiliate: Alaska Resin Supply, 201 E. Swanson Ave., Suite 1, Wasilla, AK • M-F, 9-5

How did you hear about GH Alaska? \_\_\_\_\_